

Minimum Safety Equipment Requirements Watercycles

*If every person on board a personal watercraft is wearing a lifejacket or a PFD of an appropriate size, you are only required to carry:

- 1. a sound-signalling device; and
- 2. a watertight flashlight if the boat is used after sunset or before sunrise or in periods of restricted visibility.

PERSONAL LIFESAVING APPLIANCES:

- 1. One (1) lifejacket or PFD for each person on board*
- 2. One (1) reboarding device (See Note 1)
- 3. One (1) buoyant heaving line at least 15 m (49' 3") long

VISUAL SIGNALS:

If boat is over 6 m

- 4. One (1) watertight flashlight
- 5. Six (6) flares of Type A, B, C or D, not more than two (2) of which are Type D **OR**Three (3) flares of Type A, B, C or D, not more than one (1) of which is Type D, if boat is equipped with an electronic communication device (See Note 2)

VESSEL SAFETY EQUIPMENT:

6. One (1) bailer **OR** One manual bilge pump (See Note 3) **OR**Bilge-pumping arrangements

NAVIGATION EQUIPMENT:

- 7. One (1) sound-signalling device or appliance
- 8. Navigation lights (See Note 4)
- 9. One (1) magnetic compass (See Note 5)
- 10. One (1) radar reflector (See Note 6)

FIRE FIGHTING EQUIPMENT:

None

Note 1 - Reboarding Device

A reboarding device is only required if the vertical height that a person must climb to reboard the boat from the water (freeboard) is over 0.5 m (1'8").

Note 2 - Flares

Flares are not required for a boat that:

- is operating on a river, canal or lake in which it can never be more than one (1) nautical mile (1.852 km) from shore; or
- has no sleeping quarters and is engaged in an official competition or in final preparation for an official competition.

For a pleasure craft more than 6 m in length, the number of

pyrotechnic distress signals are reduced, if the boat is equipped with an electronic communication device, including:

- a means of two-way radio communication (e.g. cell phones, satellite phones or other satellite communication devices, VHF radios with digital select calling);
- a 406 MHz personal locator beacon, which is a personal safety device designed to alert search and rescue services and allow them to quickly locate a person in the event of an emergency; or
- a 406 MHz emergency positionindicating radio beacon, which is used to alert search and rescue services in the event of an emergency via a satellite.

Note 3 – Bailer and Manual Bilge Pump

A bailer or manual bilge pump is not required for a boat that cannot hold enough water to make it capsize or a boat that has watertight compartments that are sealed and not readily accessible.

Note 4 - Navigation Lights

Navigation lights are only required if you operate the boat after sunset, before sunrise or in periods of restricted visibility (fog, falling snow, etc.).

Note 5 - Magnetic Compass

A magnetic compass is not required if the boat is 8 m (26′ 3″) or less and you operate it within sight of navigation marks.

Note 6 – Radar Reflector

Radar reflectors are required for boats under 20 m (65' 7") and boats built of mostly nonmetallic materials. A radar reflector is not required if:

- the boat is used in limited traffic conditions, daylight and favourable environmental conditions, and where having a radar reflector is not essential to the boat's safety; or
- the small size of the boat or its operation away from radar navigation makes it impossible to install or use a radar reflector.



